

Capacity	SimpleTech Part #	Board Height (mm)	Configuration	Device Type	# of Ranks	Refresh Rate	Voltage (V)
240-Pin Registered DIMM x72 ECC							
2GB	SL72P4M256M8M-A(XXX)Y	30.00	256MX72	128X4	2	8K	1.8
2GB	SL72P5M256M8M-A(XXX)Y	18.29	256MX72	128X4 IC tower	2	8K	1.8
1GB	SL72P4K128M8M-A(XXX)Y	30.00	128X72	64X4	2	8K	1.8
1GB	SL72P4M128M8M-A(XXX)Y	30.00	128X72	128X4	1	8K	1.8
1GB	SL72P4M128M8M-B(XXX)Y	18.29	128X72	128x4	1	8K	1.8
512MB	SL72P4K64M8M-A(XXX)Y	30.00	64X72	64X4	1	8K	1.8
512MB	SL72P4K64M8M-B(XXX)Y	18.29	64X72	64X4	1	8K	1.8
512MB	SL72P8F64M8M-A(XXX)Y	30.00	64X72	32X8	2	8K	1.8
256MB	SL72P8F32M8M-A(XXX)Y	30.00	32X72	32X8	1	8K	1.8
240-Pin Unbuffered DIMM x72 ECC							
1GB	SL72Q8M128M8M-A(XXX)Y	30.00	128X72	64X8	2	8K	1.8
512MB	SL72Q8M64M8M-A(XXX)Y	30.00	64X72	64X8	1	8K	1.8
512MB	SL72Q8F64M8M-A(XXX)Y	30.00	64X72	32X8	2	8K	1.8
256MB	SL72Q8F32M8M-A(XXX)Y	30.00	32X72	32X8	1	8K	1.8
240-Pin Unbuffered DIMM x64 Non-ECC							
1GB	SL64Q8M128M8L-A(XXX)Y	30.00	128X64	64X8	2	8K	1.8
512MB	SL64Q8M64M8L-A(XXX)Y	30.00	64X64	32X8	1	8K	1.8
512MB	SL64Q8F64M8L-A(XXX)Y	30.00	64X64	32X8	2	8K	1.8
256MB	SL64Q8F32M8L-A(XXX)Y	30.00	32X64	32X8	1	8K	1.8
200-Pin Unbuffered SODIMM x64 Non-ECC							
1GB	SL64H8M128M8L-A(XXX)Y	30.00	128X64	64X8	2	8K	1.8
512MB	SL64H8M64M8L-A(XXX)Y	30.00	64X64	64X8	1	8K	1.8
512MB	SL64H8F64M8L-A(XXX)Y	30.00	64X64	32X8	2	8K	1.8
256MB	SL64H8F32M8L-A(XXX)Y	30.00	32X64	32X8	1	8K	1.8
244-Pin Unbuffered Mini-DIMM x72 ECC							
1GB	SL72V8M128M8M-A(XXX)Y	30.00	128X72	64x8	2	8K	1.8
512MB	SL72V8M64M8M-A(XXX)Y	30.00	64X72	64x8	1	8K	1.8
512MB	SL72V8F64M8M-A(XXX)Y	30.00	64X72	32x8	2	8K	1.8
256MB	SL72V8F32M8M-A(XXX)Y	30.00	32X72	32x8	1	8K	1.8
244-Pin Unbuffered Mini-DIMM x64 Non-ECC							
1GB	SL64V8M128M8L-A(XXX)Y	30.00	128X64	64x8	2	8K	1.8
512MB	SL64V8M64M8L-A(XXX)Y	30.00	64X64	64x8	1	8K	1.8
512MB	SL64V8F64M8L-A(XXX)Y	30.00	64X64	32x8	2	8K	1.8
256MB	SL64V8F32M8L-A(XXX)Y	30.00	32X64	32x8	1	8K	1.8
244-Pin Registered Mini-DIMM x72 ECC							
1GB	SL72T8M128M8M-A(XXX)Y	30.00	128X72	64x8	2	8K	1.8
512MB	SL72T8M64M8M-A(XXX)Y	30.00	64X72	64x8	1	8K	1.8
512MB	SL72T8F64M8M-A(XXX)Y	30.00	64X72	32x8	2	8K	1.8
256MB	SL72T8F32M8M-A(XXX)Y	30.00	32X72	32x8	1	8K	1.8

SimpleTech provides standard, application specific and custom configurations, as well as a low-profile design expertise

Product Key

Part #: SL72P4M256M8M-A(XXX)Y

(XXX)= 05A: PC2-3200 (CL3)
37F: PC2-4200 (CL4)



Worldwide Headquarters

STEC, Inc.
3001 Daimler Street
Santa Ana, California 92705 USA
Tel: (949) 476-1180
Fax: (949) 476-1209
Web: www.stec-inc.com

STEC Europe

Donau-City-Strasse 1
1220 Vienna, Austria
Tel: +43-1-263-38-08
Fax: +43-1-263-37-65
Web: www.stec-inc.com

STEC Hong Kong

Unit 01-02, 10/F, 88 Hing Fat Street
Causeway Bay, Hong Kong
Tel: +852-3150-8398
Fax: +852-3150-8399
Web: www.stec-inc.cn

STEC Japan

YOKOHAMA, Landmark Tower
20/F 2-2-1, Minato-Mirai, Nishi-ku
Yokohama, 220-8120, Japan
Tel: +045-670-7030
Fax: +045-670-7001
Web: www.stec-inc.jp

STEC Taiwan

4F, No. 3, Lane 91, Dongmei Road
Hsinchu City, Taiwan
Tel: +886-3-5733233
Fax: +886-3-5733633
Web: www.stec-inc.com